PIG® Grippy® Adhesive-Backed Absorbent Mat Roll - Blue

MAT3251

Specifications

Weight	0.500000
Absorbency	1.3 L/Bag
Color	Blue
Fluids Absorbed	Oil, Coolants, Solvents, Water & Most Chemicals
Composition	Absorbent - Polypropylene with Polyester Stitching; Adhesive Backing - Proprietary Adhesive Material
Contents/Package	1 Roll
Dimensions	81 cm W x 102 cm L
Warnings & Restrictions	**PIG Grippy Adhesive-Backed Floor Mat & PIG Grippy Adhesive-Backed Absorbent Mat Notice:** New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use. PIG Grippy Adhesive-Backed Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 12 weeks. PIG Grippy Adhesive-Backed Absorbent Mats should be replaced if they become saturated or show signs of wear or damage. Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises. **Storage Temperature:** Store between 0° C bis 49° C **Temperature Limit:** Surface temperatures from 13° C bis 49° C
Purpose	Universal

Weight of Mat	Medium-weight
Recycled Content	25% or more Recycled Content
Sold as	0

Description

Adhesive-backed absorbent mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls in workstations and around machinery

Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive. PIG Grippy Mat will stick to most common commercial floor surfaces, including: concrete, vinyl tile, ceramic tile, quarry tile and linoleum

Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and light-wheeled traffic as well as heavy equipment driveovers

Layers of fine-fibre polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water

Traps oil, grease and grime to keep them from being tracked around

Leakproof backing prevents absorbed liquid from soaking through to the floor

New Pig Ltd.
Hogs Hill • Watt Place • Hamilton International Technology Park
Blantyre • Glasgow • United Kingdom • G72 0AH

+44 (0)800 919 900

newpig.co.uk
pigpen@newpig.com

New Pig B.V.
Concorde 5 • 5126 RM Gilze • The Netherlands

+31 (0)76 596 9250 (English)
+33 (0)800 90 30 22 (French)
+49 (0)800-1-827-487 (German)
+39 800 874 60 (Italian)

newpig.eu
pigpost@newpig.com

New Pig